Table of contents

Features 1

Applications 1

Table of contents 2

1 ÃMaximum ratings 3

2 ÃPackaging Characteristics 4

3 ÃElectrical characteristics 5

4 ÃPackage drawing 7

5 ÃTest conditions 8

Revision history 9

Attention .....

2 ÃPackaging Characteristics

Table 2 Package Characteristics


Symbol	Description	Value	Unit	Note
R_{HS}	High-side Resistance	1.6		
R_{LS}	Low-side Resistance	1.6		
Ls	Stray inductance	18	nH	
V_{ISO}	Isolation Test Voltage RMS, f=50Hz, t=1min	3.4	kV	
Distance	Terminal to Heatsink Creepage Distance	14.5	mm	
	Terminal to Terminal Creepage Distance	13.0	mm	
	Terminal to Heatsink Clearance	12.5	mm	
	Terminal to Terminal Clearance	10.0	mm	
R_{th}	Average Thermal Resistance of Per Upper Switch	0.106		
	Average Thermal Resistance of Per Lower Switch	0.101		
T_{jmax}	Maximum Junction Temperature	175		
T_{jop}	Operation Junction Temperature	-40 to +175		
T_{STG}	Storage Temperature Range	-40 to +175		
W	Weight	380	g	
Ms	Maximum Mounting Torque	6.0	N·m	

[1] Not subject to production test. Parameter verified by design/characterization.

S1P02R170HBG-D ÄPreliminary Å

S1P02R170HBG-D ÄPreliminary Å

4 ÃPackage drawing



S1P02R170HBG-D ÄPreliminary Å

1700V SiC Power MOSFET Module

Revision history

Document version	Date of release	Description of changes	
V01_00	2024-11-30	ü ü	

Attention

1. **RoHS compliance**

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/ EC (RoHS2), as implemented January 2, 2013.

2. **REACH compliance**

REACH substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, please contact a Sichain representative to insure you get the most up-to-date REACH SVHC Declaration. REACH banned substance information (REACH Article 67) is also available upon request.

3. With respect to information regarding the application of the product, Sichain hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

4. Any information given in this documents subject to customer's compliance with its obligations and any applicable legal requirements, norms and standards concerning any use of the product of Sichain in any customer's applications.

5. Specifications of any and all products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment.

6. Due to technical requirements products may contain dangerous substances. For information on the types in question please contact Sichain office.

7. Except as otherwise explicitly approved by Sichain in a written document signed by authorized representatives of Sichain, Sichain' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.

8. For use of our products in applications requiring a high degree of reliability (as exemplified below), please contact and consult with a Sichain representatives, for example but not limited to: transportation equipment, primary communication equipment, traffic lights, fire/crime prevention, safety equipment, medical systems, and power transmission systems.