N Channel Enhancement

- High speed switching
- Very low switching losses
- High blocking voltage with low on-resistance
- Temperature independent turn-off switching losses
- Halogen free, RoHS compliant

- Cooling effort reduction
- Efficiency improvement
- Reduced cooling requirements
- Increased power density
- Increased system switching frequency

- EV motor drive
- PV string inverters
- Solar power optimizer
- Switch mode power supplies




Figure 7. Transfer characteristic for various junction temperatures




Figure 8. Body diode characteristic at T_J = -55 ºC




Figure 9. Body diode characteristic at T_J = 25 ºC




Figure 10. Body diode characteristic at T_J = 175ºC




Figure 11. Threshold voltage vs. temperature




Figure 12. Gate charge characteristic




Figure 13. 3rd quadrant characteristic at T_J = -55 ºC




Figure 14. 3rd quadrant characteristic at T_J = 25 ºC




Figure 15. 3rd quadrant characteristic at T_J = 175 ºC




Figure 16. Output capacitor stored energy




Figure 17. Capacitances vs. drain-source voltage (0 - 200V)






Figure 18. Capacitances vs. drain-source voltage (0 - 1200V)

Die size W x L	5 * 5	mm	
Gate pad size W x L	0.78 * 0.68	mm	
Source pad size W x L	1.9 * 3.1	mm	
Kelvin pad size W x L	1.25 * 0.70	mm	
Die thickness	150 ± 20	μm	
Top side gate & kelvin source metallization	4	μm	AlCu
Top side power source metallization	4/4/0.35/0.05	μm	AlCu/Ni/Pd/Au
Back side drain metallization	1	μm	Ag



Symbol	Dimension / mm
B	5
b1	3.1
b2	0.7
b3	0.68
A	5
a1	0.78
a2	1.25
a3	1.9






Figure 2

1.

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/ EC (RoHS2), as implemented January 2, 2013.

2.

REACh substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notices of their intent to

6. Due to technical requirements products may contain dangerous substances. For information on the types in question please contact Sichain office.

7. Except as otherwise explicitly approved by Sichain in a written document signed by authorized representatives of Sichain, Sichain' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.

8. For use of our products in applications requiring a high degree of reliability (as exemplified below), please contact and consult with a Sichain representatives, for example but not limited to: transportation equipment,primary communication equipment,traffic lights,fire/crime prevention, safety equipment, medical systems, and power transmission systems.